## **TECHNICAL PARAMETERS OF WATER HEATERS**

| Parameters for the water heater and storage tank  |  |             |                      |
|---|--|-------------|----------------------|
| Model(s):   | CTC Safir 300L   |             |                      |
| Conventional water heater:                        | Yes  | _           |                      |
| Heat pump water heater:                           | No   | _           |                      |
| Solar water heater:                               | No   | ┨           |                      |
| Storage tank:                                     | No   | Back-up imm | ersion heater: NA    |
| General data                                      |  |             |                      |
| Declared load profile                             | -  | XXL         |                      |
| Energy efficiency class                           | -  | D           | <b>]</b> -           |
| Energy efficiency                                 | $\eta_{wH}$  | 37          | %                    |
| Annual electricity consumption                    | AEC  | 5914        | kWh                  |
| Factory thermostat setting                        |  | 70          | °C                   |
| Sound power level indoors                         | $L_WA$   | 15          | dB                   |
| Daily electricity consumption                     | $Q_{\text{elec}}$  | 26,882      | kWh                  |
| Fossil and/or biomass fuel heated water heater    |  |             |                      |
| Daily fuel consumption                            | $Q_{fuel}$   | NA          | kWh                  |
| Emissions of nitrogen oxides (dioxide)            | $NO_X$   | NA          | mg/kWh               |
| Solar heated water heater                         |  |             |                      |
| Collector aperture area                           | A <sub>sol</sub>   | NA          | m <sup>2</sup>       |
| Zero-loss efficiency                              | $\eta_o$   | NA          | ]-                   |
| First-order coefficient                           | $a_1$  | NA          | W/(m² K)             |
| Second-order coefficient                          | a <sub>2</sub>   | NA          | W/(m <sup>2</sup> K) |
| Incidence angle modifier                          | IAM  | NA          | <b> </b> -           |
| Pump power consumption                            | (solpump)  | NA          | ]w                   |
| Standby power consumption                         | (solstandby)   | NA          | w                    |
| Heat pump heated water heater                     |  |             |                      |
| Sound power level outdoors                        | L <sub>WA</sub>  | NA          | dB                   |
| Technical paremeter at declared load profile      |  |             |                      |
| Storage water heater (3XS, XXS, XS)               | Volym  | NA          | L                    |
| Storage water heater (S, M, XL, XXL, 3XL, 4XL)    | Mixed vol 40°<br>DHW   | 481         | L                    |
| Smart controller                                  |  |             |                      |
| Weekly fuel consumption with smart                | Q fuel, week, smart  | NA          | kWh                  |
| Weekly electricity consumption with smart         | Q elec, week, smart  | NA          | kWh                  |
| Weekly fuel consumption without smart             | Q <sub>fuel, week</sub>  | NA          | kWh                  |
| Weekly electricity consumption without smart      | Q <sub>elec, week</sub>  | NA          | kWh                  |
| Technical parameters for storagetank              |  |             | 1                    |
| Standing loss                                     | S  | NA          | w                    |
| Storage volume                                    | V, C <sub>act</sub>  | NA          | <u> </u> _           |
| Specific precautions and end of life information: | The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. Disposing of the product as household waste is not permitted. |             |                      |
| Detailed Contact data:                            | Enertech AB, Box 309, 341 26 Ljungby www.ctc.se 180426   |             |                      |